

Installation and Care



Due to the products steel construction and heavy weight, care should be taken to ensure certain details are met prior to final installation of the registers and grilles. These requirements will ensure that the product will be installed correctly and safely.

-Prior to products installation, we highly recommend that flat black paint be applied to the interior of the duct work where the register or grille will be installed. This will ensure that any unsightly items will not show through the face of the product. Make sure your system and blower fan is switched to the OFF position when performing this painting.

-All registers and grilles mounting screws must be installed. Counter sunk screw holes and color-matched screws are provided in the correct quantity to support the weight of the product.

-When installing the color-matched screws with a power drill, make sure to use lower clutch settings and use a #2 Phillips bit to avoid damage to the screw face. If for some reason the paint is chipped on the screw head during installation, use of a similar-colored felt tip pen for touch up works well.

-Framing members, or “blocking”, must be securely installed on all four sides of the sheet metal “can” and must be tied into adjacent framing. Plaster grounds must be installed on all 4 sides of the sheet metal “can”. All screws must securely penetrate the plaster grounds and penetrate the wood framing to ensure all screws securely support the weight.

-If the framing detail above is not met, some type of drywall anchor such as “EZ Anchor” must be installed into the drywall prior to the mounting screws being installed. These anchors must be installed properly and sufficient to support the weight of that register or grille.

-No exceptions to these installation practices should be considered. A failure to follow these details can result in a register or grille falling from its location, resulting in property damage and/or serious injury.

-For general cleaning and maintenance of your products, we suggest a vacuum with a brush attachment to remove dust build up or, if needed, a soapy warm water cleaning. Please make sure to avoid using any abrasive material or harsh chemicals to clean the face of the product, as this may result in damage to the finish.

-Most accessories are designed to be removed for cleaning. Concealment louvers, air directionals, speaker cloth backers, and wire mesh backers can all be removed for cleaning. Simply remove the small black screws holding them to the frame of the register or grille and clean them, then reinstall in the reverse order.